

Care.

Trust.

Responsibility.



Harmony

Kitchen Display Solution

Harmony is Partner Tech's innovative Kitchen Display Solution, which includes the KDS-1000 controller, the BB-20 Bump Bar, and Harmony Software Application providing a single solution for demanding kitchen environments.

This affordable and powerful integrated system is designed to enhance the efficiency of a busy restaurant kitchen while also increasing customer satisfaction and service. The KD-1000 aluminum housing is spill-proof and designed for harsh, greasy environments. The unit's solid construction prevents damage from system heat and no moving parts ensures a long system life.

Harmony is a unique, full featured Kitchen Video System designed from the start to excel in both full service and quick service kitchens. Chit based screens mimic the paper flow your kitchen staff is already using which eases the transition to new technology. Special colors and other cues on the screen help control timing and synchronization of items on each order throughout the entire kitchen, eliminating kitchen quarterbacking and dramatically increasing food quality. Reporting is available to keep management informed on the performance of their operations and help identify and resolve trouble areas.



Specifications

Item	Harmony Controller
Processor	VIA V4 ULV 1 GHz
Chipset	NB -CD7220, SB -VIA VT8237R plus
System Memory	DDR2 Long DIMM 512MB, up to 1GB
BIOS	Award System BIOS, 4M bits flash ROM
Storage	4G uSSD standard, CF Card (optional)
Network	Ethernet 10/100M
LED Indicator	• 1 * Power LED • 1 * Flash LED • 1 * Lan LED (Green)
I/O Interface	<ul style="list-style-type: none"> • 2 * RJ45 COM ports (COM 1 & 2 are powered with DC +5V or DC +12V • 2 * DB-15 VGA ports ; supports 2 monitors • PS2 keyboard port • PS2 mouse port • RJ-45 LAN port • 3 * USB ports (1 port in front, 2 ports in rear) • 2 * Audio ports (1 line-out, 1 mic-in) • 1 * DC +12V power adaptor connector • 1 * 802.11g WLAN antenna connector (optional)
Operating System	WIN CE.Net 5.0, WEPOS
Power Supply	AC 100V-240V / DC 12V / 4.16A 50 watt power adaptor
Accessories	Power adaptor, RS-232 cable, CD, I/O connector covers, QSG
Wall Mount Capable	Wall mount design option with VESA 75 hole mount
Peripherals	20 key Bump Bar (optional)
Operating Temperature	32° F ~ 104° F
Storage Temperature	-4° F ~ 140° F
Humidity	10% ~ 80%
Dimensions	2.3" (H) x 7.4" (W) x 9.1" (L)
Weight	Approx. 4.18 lbs
Certifications	CE, FCC, UL, CB, BSMI, VCCI

Item	Bump Bar
Interface	Serial
Number of Keys	20
Key Stroke Life	50 million cycles
Storage Temperature	-40° F ~ 158° F
Operating Temperature	32°F ~ 158° F
Dimensions	2.9" (W) x 1" (H) x 9.9" (L)
Weight	Approx. 1.55 lbs

For More Information

www.harmonykds.com



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.